

# DUAL PALLET HANDLING

0612201701

Model	Capacity on LC 600 mm (kg)	Section D1/D2 x S (mm)	Lost load thickness (mm)	CoG1 ± (mm)	CoG2 ± (mm)	Weight ± (kg)	ISO/FEM
<b>"Hydraulic fork extensions" applications</b>							
REE2 17 0800/0400	1700	128/128x40	40	215	240	90	2A
REE2 17 1000/0200				290	310	105	
REE2 17 1200/0800				375	495	116	
REE2 24 0800/0400	2400	131/131x44	45	220	275	104	2A
REE2 24 1000/0200				300	325	121	
REE2 24 1200/0800				385	510	135	
RGE2 20 0800/0400	2000	131/131x57	45	233	293	113	2A
RGE2 20 1000/0200				316	340	133	
RGE2 20 1200/0800				397	520	145	
RGE2 30 0800/0400	3000	131/131x57	45	220	275	122	3A
RGE2 30 1000/0200				302	327	144	
RGE2 30 1200/0800				382	515	158	

Model	Capacity on LC 24" (Lbs)	Section D1/D2xS (In)	Retracted/Stroke L / K (In)	C (In)	CoG1 (In)	CoG2 (In)	Weight (Lbs)	Mounting Class
<b>"Hydraulic fork extensions" applications</b>								
REE2 17 0800/0400	3,750	5.0/5.0x1.6	31.5/15.7	1.6	8.5	9.4	200	2A
REE2 17 1000/0200			39.4/7.9		11.4	12.2	230	
REE2 17 1200/0800			47.2/31.5		14.7	19.5	255	
REE2 24 0800/0400	5,280	5.16/5.16x1,7	31.5/15.7	1.8	8.7	10.8	229	2A
REE2 24 1000/0200			39.4/7.9		11.8	12.8	266	
REE2 24 1200/0800			47.2/31.5		15.2	20.1	297	
RGE2 20 0800/0400	4,400	5.16/5.16x2.2	31.5/15.7	1.8	9.2	11.5	325	2A
RGE2 20 1000/0200			39.4/7.9		12.4	13.4	343	
RGE2 20 1200/0800			47.2/31.5		15.6	20.5	375	
RGE2 30 0800/0400	6,600	5.16/5.16x2.2	31.5/15.7	1.8	8.7	10.8	340	3A
RGE2 30 1000/0200			39.4/7.9		11.9	12.9	360	
RGE2 30 1200/0800			47.2/31.5		15.0	20.3	395	